

SVETLANA TECHNICAL DATA

6N1P Dual Audio Triode



The Svetlana™ 6N1P is a miniature glass-envelope small-signal dual triode intended for use as a line-level amplifier or driver in high-quality audio amplifiers. Except for higher heater-current consumption, it is a direct plug-in replacement for the 6DJ8, ECC88 or 6922 in most high-level audio applications. Features include very low distortion—optimized for line stages; medium transconductance; internally shielded between sections, allowing their use at differing signal levels; higher plate-voltage and dissipation rating than 6DJ8 types; and larger cathode than 6DJ8 types, giving it longer life and more transient current capability.

Characteristics

Electrical

Cathode	Oxide-coated, unipotential
Heater voltage (AC or DC)	6.3 volts AC or DC (± 0.6 volts)
Heater current	600 mA \pm 35 mA
Heater-cathode voltage	± 100 volts peak
Amplification factor (nominal)	33
Transconductance (nominal)	7500 μ S
Plate resistance (nominal)	4400 ohms
Interelectrode capacitances (typical), per section, with cathode grounded:	
Grid to cathode	3.2 pF
Anode to cathode	1.5 pF
Grid to anode	1.6 pF



Mechanical

Base	standard 9-pin miniature, glass button
Basing diagram	JEDEC 9AJ
Socket	9-pin miniature
Operating position	Any
Nominal dimensions:	
Height of glass envelope	49 mm (1.93 in.)
Diameter of glass envelope	22.5 mm (.88 in.)
Overall height	56 mm (2.20 in.)
Net weight	15 g (.50 oz.)

Maximum ratings

Anode voltage, DC	250 V
Anode dissipation, per triode	2.2 W
Cathode current, continuous, per triode	20 mA
Maximum grid-circuit resistance	0.5 megohm

Svetlana Outline drawing



Svetlana 6N1P Dual Audio Triode

